



## SOLEX 660 MULTI-PURPOSE GEAR OIL

Solex 660 is a multi-purpose gear oil formulated with selective paraffinic mineral base stocks for minimum wears on gears. It is designed to withstand the most severe shock loads that at most other conventional types of lubricants will tend to break down and allow metal to metal contact.

Solex 660 is blended with high quality adhesive-cohesive agents that make it immediately climb and cling to gears to give maximum protection. It remains tackiness on gears to provide easy start and operating at high temperatures. Solex 660 has a low pour point, which permits efficient starting in a low temperature condition

### TECHNICAL SPECIFICATIONS

Appearance		Red tacky
Specific gravity @ 15 ° C	ASTM D 1298	0.905 g/ml
Viscosity Index	ASTM D 2270	96
Viscosity @ 40 ° C	ASTM D445	439 cst
Flash point	ASTM D 92	246 ° C

### AREAS OF APPLICATIONS

Use Solex 660 to lubricate various types of gears, including worm gears, hypoid gears, gear heads, spur gears, bevel gears, etc.

Solex 660 allows transmissions, differentials and gearboxes to run at maximum efficiency for maximum service life.

*The data published are to our best knowledge the correct information. We reserve the right to alter the specifications any time and without prior notice.*

